



Profil Section AA/HAA		Profil Section BB/HBB		Profil Section CC/HCC		Profil Section DD/HDD	
Bezugslänge Reference length (mm)	Riemen-Nr. Belt no.	Bezugslänge Reference length (mm)	Riemen-Nr. Belt no.	Bezugslänge Reference length (mm)	Riemen-Nr. Belt no.	Bezugslänge Reference length (mm)	Riemen-Nr. Belt no.
2000	77	1980	75	2280	86	auf Anfrage on request	
2032	78	2180	83	2500	94		
2370	91	2300	88	2800	106		
2500	96	2370	90	3200	122		
2650	102	2500	95	3310	126		
2667	103	2540	97	3765	144		
2800	108	2600	99	4000	153		
3300	128	2650	101	4216	162		
3920	152	2740	105	4300	165		
		2800	107	4500	173		
		2850	109	5000	193		
		2920	112	5300	204		
		3000	115	5340	206		
		3030	116	5750	224		
		3150	121				
		3250	125				
		3280	126				
		3325	128				
		3390	131				
		3450	133				
		3500	135	Gewicht Belt weight: ≈ 0,440 kg/m		Gewicht Belt weight: ≈ 0,935 kg/m	
		3550	137	Profil Section 22 x 22		Profil Section 25 x 22	
		3730	144				
		3750	145				
		4010	155				
		4040	156	5180		auf Anfrage on request	
		4200	162	5220			
		4470	173	5850			
		4500	174	6270			
		4750	184				
		5000	194				
		5639	221				
Gewicht Belt weight: ≈ 0,150 kg/m		Gewicht Belt weight: ≈ 0,250 kg/m		Gewicht Belt weight: ≈ 0,511 kg/m		Gewicht Belt weight: ≈ 0,625 kg/m	

Zwischenlängen und Sonderausführungen ab: Non-standard lengths available:		Umrechnungswerte von der Riemen-Nr. zur Bezugslänge: To convert from belt no. (that is theoretical inside length in inches) to reference length:	
Profil Section AA/HAA	1350 bis up to 28 000 mm	Profil Section AA/HAA –	Riemen-Nr. belt no. x 25,4 = mm + 53 mm
Profil Section BB/HBB	1350 bis up to 28 000 mm	Profil Section BB/HBB –	(bis Riemen-Nr. up to belt no. 210)
Profil Section CC/HCC	2000 bis up to 28 000 mm		Riemen-Nr. belt no. x 25,4 = mm + 74 mm
Profil Section 22 x 22	3000 bis up to 10 000 mm		(über Riemen-Nr. over belt no. 210)
			Riemen-Nr. belt no. x 25,4 = mm + 36 mm
		Profil Section CC/HCC –	(bis Riemen-Nr. up to belt no. 210)
			Riemen-Nr. belt no. x 25,4 = mm + 107 mm
			(über Riemen-Nr. over belt no. 210)
			Riemen-Nr. belt no. x 25,4 = mm + 56 mm
		Profil Section DD/HDD –	(bis Riemen-Nr. up to belt no. 210)
			Riemen-Nr. belt no. x 25,4 = mm + 132 mm
			(über Riemen-Nr. over belt no. 210)
			Riemen-Nr. belt no. x 25,4 = mm + 69 mm