

## U8



### UNIVERSAL SUCTION CUP

- ▶ Suitable for objects with flat or slightly curved surfaces.
- ▶ Also used for concave objects.

### LIFTING FORCES & TECHNICAL DATA

Lifting force vertical to the surface, N, at vacuum level			Lifting force parallel to the surface, N, at vacuum level			Volume cm <sup>3</sup>	Min. curve radius mm	Max. vertical movement mm	Weight rubber part g
20 -kPa	60 -kPa	90 -kPa	20 -kPa	60 -kPa	90 -kPa				
1.0	2.9	3.9	1.0	2.9	3.4	0.10	6.0	0.50	0.16

### MATERIAL SPECIFICATIONS


Material	Colour	Hardness °Shore A	Temperature range °C
Chloroprene, CR	Black	50	-40-110
Silicone, SIL	Red	50	-40-200

### MATERIAL RESISTANCE


Material	Wear resistance	Oil	Weather & ozone	Hydrolysis	Petrol	Concentrated acids	Alcohol	Oxidation
Chloroprene, CR	Excellent	Fair	Good	Good	Fair	Poor	Good	Good
Silicone, SIL	Good	Poor	Excellent	Fair	Poor	Poor	Good	Excellent

## ORDERING INFORMATION

Complete suction cups	Art. No.
Suction cup U8 Chloroprene, M5 male	3150004
Suction cup U8 Silicone, M5 male	3150004S



Rubber parts	Art. No.
Suction cup U8 Chloroprene	3150116
Suction cup U8 Silicone	3150116S



Fittings	Art. No.
Fitting M5 male, 5-8	3107031

For further information and dimensioned drawings, see *SUCTION CUPS FITTINGS* chapter.